



<b>Form size:</b>	ATX 12V Ver. 2.31 EPS 12V Ver. 2.91 and SSI Ver. 2.92
<b>Power:</b>	1000W
<b>Input power:</b>	115/240 Vac
	12A
	Frequency 50/60Hz
<b>Output power:</b>	+3.3V: 24A
	+5V: 30A
	+12V1: 20A
	+12V2: 20A
	+12V3: 20A
	+12V4: 35A
	+12V5: 35A
	+12V6: 20A
	-12V: 0.5A
	+5VSB: 5.0A
<b>Output connections:</b>	1x 20/24pin MB
	1x 12V 4+4pin CPU
	1x 12V 8pin CPU
	8x SATA
	8x 4pin peripherals
	3x 6pin PCIe
	3x 6+2pin PCIe
	1x FDD

<b>PFC:</b>	Active
<b>Cooling:</b>	140mm green smart fan with automatic speed
<b>Noise level:</b>	< 21dBA
<b>Protections:</b>	Over voltage; under voltage; overload; short circuit, input voltage
<b>Dimensions:</b>	85 (H) x 150 (L) x 163 (D) mm
<b>Extra features:</b>	<ul style="list-style-type: none"> <li>- Modular cable management</li> <li>- Supports multiple graphic card (SLI/Quad SLI/CrossFire X)</li> <li>- Active PFC</li> <li>- 140mm green smart fan with automatic speed</li> <li>- 80PLUS Bronze certified</li> <li>- 6 separate 12V lines</li> <li>- SATA connectors</li> </ul>

